



PED200 FIBER OPTIC PEDESTAL

The Tempo Communications fiber optic pedestal (PED200) provides secure storage for passive fiber optic equipment in FTT(x) installations. The IP55 and IK10 specifications insures a water resistant and rugged installation to protect the installed equipment.

FEATURES

- IP55 water resistant design for superior protection.
- IK10 Impact resistance provides field ready ruggedness.
- Universal mounting bracket.
- Composite materials provide long life and superior UV protection.
- Locking cover with 3/8" nut.

SPECIFICATIONS

CAT. NO.	DESCRIPTION
IP rating	IP55
Impact Resistance	IK10
Dimensions	27.5" (700mm) x 12" (410mm)
Weight	11.9lbs 5.4kg
Material	ABS
Color	Light green
UV Aging	1000 hours
Spike Length	9.8" (250mm)
Locking Nut	3/8" hex
Shipping Box Size	21.6" (55cm) x 13.0" (33cm) x 13.0" (33cm)
Shipping Box Weight	13.7lbs (6.2kg)

ORDERING INFORMATION

CAT. NO.	DESCRIPTION
PED200	27.5" (700mm) x 12" (410mm) Pedestal



KIT PARTS

- Top and bottom pedestal shells
- Spike
- Universal mounting bracket
- Mounting hardware



3/8" Hex nut compatible with the PA1900 can wrench.



Shell and base nest for compact shipping.

1390 Aspen Way Vista, CA • 92081 **PED200 04/23**
Latin America Phone: 1 760 510 0558 | EMEA Phone: +44 (0) 1633 927 050
India and SAARC Region Sales: indiaSales@tempocom.com

EMEA: Tempo Europe Limited • Brecon House
William Brown Close • Cwmbran • NP44 3AB • UK

©2023 Tempo Communications Inc. • An ISO 9001 Company

TempoCom.com | [tel 800.642.2155](tel:800.642.2155) | sales@tempocom.com



TEMPO

COMMUNICATIONS

Renewed Vision. Innovation Forward.



Follow us @TempoComms