



BARE FIBER ADAPTER

Instrumentation &
Network Interconnects

TESTING | TROUBLESHOOTING | ACCURACY

Benefits

- Provides a fast method of temporarily connecting a fiber under test to a test instrument
- Measure the length of fiber on a spool with an OTDR without having to connectorize the fiber spool
- Measure the optical power present on a fiber without a connector
- Temporarily connect a VFL to a fiber so that the technician can inject visible light onto a fiber that does not have a connector

Applications

- Temporarily connect test instruments such as OTDR's, OPM's, and VFL's to fiber under test

Specifications:

Fiber Sizes	Singlemode and multimode fibers with a 250 micron outside diameter
Connector	SC/PC



Order Information:

CAT. NO.	DESCRIPTION
BFA-1	Bare Fiber Adapter

1390 Aspen Way Vista, CA • 92081

TC-BFA 09/21

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927050

©2019 Tempo Communications Inc. • An ISO 9001 Company

EMEA Address: Tempo Communications Limited • Brecon House,
William Brown Close, Cwmbran • NP44 3AB, UK

TempoCom.com | tel 800.642.2155



Renewed Vision. Innovation Forward.



Follow us on Social Media
[@TempoComms](https://twitter.com/TempoComms)