



**FIBER TOOLS**

# LC-500 Launch Cable

TESTING | TROUBLESHOOTING | ACCURACY

## Product Features:

### ELIMINATE DEAD ZONES:


Long OTDR pulse widths are suppressed

### UNIVERSAL, COMPACT DESIGN:

No need for multiple launch cables for varying network connectors

Typically the technician will use a launch cable on the input and output connectors of the fiber under test. This allows the technician to characterize the insertion and return loss of the input and output connectors of fiber link. Supports SC, LC, FC, and ST connectors (APC + UPC as appropriate).

It is recommended that a one meter patch cord is used at the 930XC OTDR bulkhead. Please refer to the application note "Using a one meter Jumper at the bulkhead".



## ORDERING INFORMATION:


CAT. NO.	DESCRIPTION
LC-500	500m Launch Cable, Singlemode



OFL100

1M PATCH CORD

INPUT  
LAUNCH  
CABLE



Fiber Under Test

OUTPUT  
RECEIVE  
CABLE

1390 Aspen Way Vista, CA • 92081

TC6451 06/22

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 627710

©2019 Tempo Communications Inc. • An ISO 9001 Company

EMEA Address: Tempo Communications Limited • Brecon House, William Brown Close, Cwmbran • NP44 3AB, UK

TempoCom.com | tel 800.642.2155



**TEMPO**  
COMMUNICATIONS

*Renewed Vision. Innovation Forward.*



Follow us on Social Media  
@TempoComms