



**FIBER TOOLS**

# MICRO OPTICAL POWER METER

Essential Tools for the Premise Technician

TESTING | TROUBLESHOOTING | ACCURACY

## Product Features:

- Wide measurement range (+10 to -70dBm)
- High power CATV range (+26 to -50dBm)
- VFL for safe and effective fault locating
- Singlemode and multimode compatible
- Available wavelengths of 850, 980, 1270, 1300, 1310, 1490, 1550, 1577, 1625, 1650nm
- 270Hz, 1kHz and 2kHz tone detect
- Auto power off

## CONTENTS:

- Micro OPM with VFL
- Lanyard
- Instruction Sheet

## ORDERING INFORMATION:

CAT. NO.	DESCRIPTION
OPM210	Standard Power OPM with VFL
OPM220	High Power OPM with VFL
1.25MM ADAPTER	1.25mm Adapter
08325	Micro OPM Carry Case
CAL CERT	Calibration Certificate



Follow us on Social Media  
**@TempoComms**



**TEMPO**  
COMMUNICATIONS

*Renewed Vision. Innovation Forward.*



# FIBER TOOLS

## SPECIFICATIONS:

PARAMETER	SPECIFICATIONS	
Model:	<b>OPM210</b>	<b>OPM220</b>
Measurement Range:	-70 to +10dBm (980, 1270, 1310, 1490, 1550, 1577, 1625, 1650)	-50 to +26dBm (980, 1270, 1310, 1490, 1550, 1577, 1625, 1650)
	-60 to +10dBm (850/1300)	-40 to +26dBm (850/1300)
Wavelengths:	850, 980, 1270, 1300, 1310, 1490, 1550, 1577, 1625, 1650nm	
Display Resolution:	0.01dB	
Uncertainty*:	+/-0.50dB	
Connector:	Universal 2.5mm	
Wavelength Response:	700 - 1700nm	
Detector:	InGaAs	
Tone Frequency	270Hz, 1kHz and 2kHz	
Power Supply:	AAA x 2 Alkaline	
Battery Lifetime:	>60 Hours (OPM mode)	
Operating Temperature:	-10 to +50°C (<90% Relative Humidity)	
Storage Temperature:	-20 to +60°C (<90% Relative Humidity)	
VFL Wavelength:	650nm +/-20nm	
VFL Output:	≤ 1mW/ 2Hz	
VFL Range:	4km	
Size:	106 x 58 x 28mm (4.17 x 2.28 x 1.10")	
Weight:	106g (0.23lbs)	
Auto Power Off:	10 minutes of no activity	
Certifications:	CE, RoHS, CDRH, WEEE	

\* At -10dBm (1310nm) when using singlemode fiber with an FC connector at 23C.  
Specifications subject to change without notice.

1390 Aspen Way Vista, CA • 92081

TC6910 11/24

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927050

©2024 Tempo Communications Inc. • An ISO 9001 Company

EMEA Address: Tempo Communications Limited • Brecon House,  
William Brown Close, Cwmbran • NP44 3AB, UK

TempoCom.com | tel 800.642.2155



**TEMPO**  
COMMUNICATIONS

*Renewed Vision. Innovation Forward.*



Follow us on Social Media  
**@TempoComms**