

SatFinder Pro: Quick Start Guide

This guide will help you get started with your new SatFinder Pro meter quickly and efficiently.

Adjusting Brightness and Display Mode

To customize your screen:

- Press the **Brightness key**.
- Use the **right arrow key** to increase brightness or the **left arrow key** to decrease it.
- Use the **side screen keys** to toggle between **Light Mode** and **Dark Mode**.

Updating Your Meter via Wi-Fi

Keeping your meter updated ensures optimal performance:

1. Press **Menu**, then select **Wi-Fi**.
2. A list of available networks will appear. Select your desired **Network ID** and enter the password.
3. Press **Save**. (You can also press **Save as a Fav** to quickly connect next time).
4. Then, press **Connect**.
5. Once connected, return to the **Wi-Fi menu screen** and press **Update**.
6. On the Flash Update page, versions with available updates will have a **checkmark**.
7. Highlight the version you want to update and press **Update**.

Note: *The main software update may take up to five minutes.*

Locking Onto a Satellite Signal

Follow these steps to acquire a signal:

1. Connect the **LNB** to the **satellite LNB port** on your meter.
2. Next, press **SYST (System Setup)** and look for the network first.
3. Under **Service**, scroll through the available networks. Highlight your desired network and press **Enter**, then press **Done** to return to the run screen.
4. Press **LNB On**. You'll see signal strength on the left and signal quality on the right.
5. Use the **up or down arrows** on the keypad to toggle through different transponders.
6. To check a second LNB for that satellite, switch to it and toggle through its transponders.

Identifying a Satellite

Once you've locked onto a signal:

1. Press the **ID key**.
2. The meter will automatically display the satellite it has found.

Signal Lock Audio Alert

To turn on an audible alert during dish pointing adjustments:

1. Press the **Audio** key.
2. An intermittent beep will be heard when the signal is not locked.
3. The tone will change to a solid beep when the dish is adjusted to the appropriate position and a lock is obtained.
4. Press the **Audio** key again to turn this feature off.

Manual Tuning

If you need to fine-tune or find specific transponders:

1. From the Main Menu, scroll using the up and down arrows to **Manual Tune** and press **Enter**.
2. Manually enter the desired **frequency, signal rate, or signal type**.
3. Once entered, exit back to the run screen, and the manually entered information will be displayed.

Switching Between Cable and Satellite Modes

Your meter supports both modes:

1. Press **Menu**.
2. Scroll up to **Switch to Cable / Off-Air** (or **Switch to Satellite**) and press **Enter**.
3. The meter will reboot and power on in the newly selected mode.

Cable Mode Specifics

In Cable Mode:

1. Press **Menu**, then scroll to **Channel Plans**.
2. Switch between **EIA Standard QAM** or **OTA Digital plan**.
3. Perform a channel scan and save found channels to a custom plan.
4. There's an option for a **preamp** that you can turn on and off, which provides voltage on the output port.
Do NOT use this if you do not have a preamp on the incoming RF signal.

Extra Features (Main Menu Options)

From the run screen, press the **Menu key** to access additional features via the side screen keys:

- **Limit Scan**
- **PoP Scan**
- **Voltage / Current Screen**
- **Spectrum**

We hope this guide helps you get the most out of your SatFinder Pro! If you have any further questions, please refer to the full user manual or contact our support team.

USA Headquarters
Tempo Communications Inc.
1390 Aspen Way, Vista, CA 92081
(+1 800 642 2155)
support@tempocom.com



www.tempocom.com

EMEA Sales Office
Tempo Europe Limited,
Suite 8, Brecon House, William Brown Close,
Cwmbran, NP44 3AB UK
(+44 1633 927 050)
emeasales@tempocom.com